

DECLARATION OF PERFORMANCE

DoP number 002

Accoya Wood panels and decking boards
with Burnblock fire protection treatment

1. Unique identification code of the product type:

Accoya modified solid wood profiles

2. Intended use or uses of the construction product:

Wood claddings for interior and exterior end use applications.

3. Name and address of the distributor and producer in Finland

Novenberg Oy
Nervanderinkatu 9 LH 1
00100 Helsinki, Finland

Tel. +358 44 244 1236
info@novenberg.fi
www.novenberg.fi

4. System of AVCP

AVCP 3

5. European assessment document

EN 14915:2013 + A2:2020

6. Declared performance

Type of wood	Radiata pine	
Intended use	Interior and exterior use	
Density	515 ± 40 kg/m ³	
Installation	Horizontal and vertical	
Reaction to fire	Class B-s1,d0 >= 19mm	EN 13501-1:2018
Equilibrium moisture content	3 – 5%	65% RH, 20°C (70oF)
Water vapor permeability	NPD	
Thermal conductivity	0,12 W/m K	EN 12667
Bending stiffness	8800 N/mm ²	EN 408
Janka hardness	Side 4100 N / End 6600 N	ASTM D143
Brinell hardness	24.0 N/mm ²	EN 1534
Sound absorption	NPD	
Hazardous substances	Complies with regulation	(EC) No 1907/2006
Durability classification	Class 1	EN350

The performance of the product is in accordance with the regulation (EU) No. 305/2011

Helsinki 5.6.2025



Karl Lindström
Country Manager Finland | Novenberg